

DECLARATION OF PERFORMANCE

No. 001/EDF

Rev. 2

1. Unique identification code of the product-type: MEG F1 thickness ≥ 2,0 mm

2. Uses: HPL laminate used as external wall and ceiling finishes

3. Manufacturer: ABET LAMINATI spa - Viale Industria, 21 - 12042 BRA (CN) - Italy Tel. +39 0172 419 111 - Fax: +39 0172 431571 - Email: abet@abet-laminati.it

4. System of AVCP: system 1

5. Harmonised standard: EN 438-7: 2005

6. Notify Body: CSI SpA - n° 0497

7. Declared performance

Essential characteristics	Performance
Reaction to fire	B-s1,d0 thickness ≥ 6 mm fixed on any kind of frame C-s2,d0 2 mm ≤ thickness < 6 mm mounted on aluminium tubular rods
Resistance to fire	NPD
Water vapour permeability	NPD
Resistance to fixings	250 N (2 mm) 2000 N (6 m) 4000 N (≥ 10 mm) 1000 N (4 mm) 3000 N (8 mm)
Direct airborne sound insulation	NPD
Flexural tensile strength	PASS
Thermal resistance/conductivity	NPD
Thermal shock resistance	PASS
Release of formaldehyde	Class E1
Durability Resistance to wet conditions Density	PASS ≥ 1350 kg/m ³

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Bra, 09/09/19

Luciano Menegaldo Technology Department